

WB180 Series



8-11/16" dia. W x 16" H x 4" D (221 x 406 x 102mm)
 Dimming requires recessed housing 3-1/4" W x 2" D
 x 11" H (83 x 51 x 279mm)

WB180-LED illustrated
 with options:
 Decorative Banding **-DB**
 Finish Color **-ABZ**

Example: WB180-LED-ABZ-DB-277

Construction

- Fixture is 20 gauge steel
- Diffusers are .125" white acrylic; other colors, textures, and materials are available
- Finish is textured powder coat polyester

Electrical

- High performance LEDs are available in a variety of colors
- Integral driver is standard universal voltage; optional 0-10v dimming driver available.

How to Specify

1. Select catalog number with option suffix(es).
2. Specify color of finish.
3. Consult your Cole representative for other design changes for your requirements.

Catalog Number

Wall Bracket	Lamps
LED 12W, (1006 lm @ 3000°K)	WB180-LED
LED 25W, (2646 lm @ 3000°K)	WB180-LED-HO
E26 medium base	WB180-LED/E26 (2 sockets)

Lumens shown are source. Church light photometric data available upon request.

Options

Decorative Banding: Adds detailed appearance. Add suffix **-DB**.

Metal Channel Accents: Provides steel side channels in lieu of wood. Add suffix **-MCA**.

Add Wood Accents: Add suffix **-AWA**.

Finish Color:

Antique Bronze Vein: Add suffix **-ABZ**.

Antique Copper Vein: Add suffix **-ACP**.

Diffusers: Alternates to standard white acrylic.

Clear sandblasted acrylic. Add suffix **-ACR**.

Other shielding. Add suffix **-OS/**_____ specify

Dimming: Universal voltage, 0-10V driver. 1%-100% range. Add suffix **-DIM**.

LED colors:

2700°K (976 lm), HO (2567 lm).

Add suffix **-27K**.

4100°K (1030 lm), HO (2710 lm).

Add suffix **-4K**.

Voltage: 277V LED driver. Add suffix **-277**.



C.W. Cole & Company, Inc.
 2560 Rosemead Boulevard
 South El Monte, CA 91733-1593

Tel. (626) 443-2473
 Fax (626) 443-9253
 info@colelighting.com
www.colelighting.com